



**CZECH UP YOUR BEER**  
COOLING AND DISPENSING SYSTEMS

# MODEL AS-110-US GREEN LINE

COOLING OUTPUT OF 60-110 L/HOUR

## ADVANTAGES AND FUNCTIONAL CHARACTERISTICS OF THE AS LINDR LINE:

**AS** – technology of water cooling with an ice bank. This machine can provide maximum cooling output.

**GREEN LINE** – LINDR GREEN LINE technology is environmentally friendly thanks to the use of eco-friendly refrigerant R-290. We have introduced an energy saving system in the production. Thanks to this design, each product achieves **20% higher energy efficiency and 20% lower energy consumption.**

**LINDR COOLING TECHNOLOGY** – always more powerful than its electric input power.

**CONSTRUCTION AND SERVICING** – the modern arrangement of LINDR cooling technology ensures ease of access for potential servicing and maintenance.

**PERFORMANCE, QUALITY, SIZE** – the best performance/ quality/ size ratio.



*These undercounter coolers are designed for professional dispensing of beverages in restaurants and bars. Models from the AS-110 series are fitted with a pump with 6 m displacement, which allows the cooler to be placed in a cellar and still cool the beverage all the way to the tap.*

✓ **COMFORTABLY PORTABLE** – easy and safe handling thanks to two stainless steel handles on the sides of the device.

✓ **TROPICAL CONDITIONS** – AS INOX TROPICAL features a thickened 45 mm insulation, even on the top cover, and is designed for extreme tropical conditions. This device can fully function even at ambient temperatures of up to 45°C.

✓ **GREEN LINE** – all models from the AS series are fully in GREEN LINE design.

✓ **EQUIPMENT** – thermostat, cooling coil, speedfit fittings, stirrer with a pump to ensure even temperature across the entire water bath and proper cooling of the beverage all the way to the tap.

# TECHNICAL PARAMETERS



## AVAILABLE CUSTOM MODIFICATION OPTIONS

### POWER CABLE PLUG

Note  
Selected models are also available in 115 V/60 Hz or 220 V/60 Hz voltage.  
Other custom modifications are also available (contact us).

YES



PRODUCT MODEL	AS-110-US GL 2x cooling coils	AS-110-US GL 4x cooling coils	AS-110-US GL 6x cooling coils
COOLING POWER OF THE COMPRESSOR (HP)	1/3	1/3	1/3
COOLING POWER OF THE COMPRESSOR (W)	860	860	860
MAXIMUM COOLING CAPACITY TO 0°C / TK 45°C (L/HOUR)	110	110	110
CONTINUOUS COOLING PERFORMANCE (L/HOUR)	60	60	60
THERMAL GRADIENT ΔT (°C)	10	10	10
ICE BANK (KG)	10-20	10-20	10-20
DISPLACEMENT OF RECIRCULATION PUMP (M)	6	6	6
NUMBER OF COOLED BEVERAGES (PCS)	2	4	6
NUMBER/ LENGTH OF COOLING COILS (M)	2/ 14	2/ 14, 2/ 11	2/ 14, 2/ 11, 2/ 8
POWER (W)	805	805	805
AMPERAGE (A)	7.0	7.0	7.0
NET WEIGHT (KG)	31,5	33,5	35,0
TYPE OF REFRIGERANT	R290	R290	R290
VOLTAGE	115V 60HZ~1	115V 60HZ~1	115V 60HZ~1
CONNECTION BEER/ AIR - SPEEDFIT FITTINGS	3/8, 1/2	3/8, 1/2	3/8, 1/2

